

PRODUCT DESCRIPTION

TREMproof® 3700 HD Seal Tape is a Double-sided adhesive tape based on polyester film carrier, protected with white release paper liner. The carrier is coated with a pressure sensitive adhesive on both sides with an excellent initial tack. The carrier film has a balance of mechanical strength and dimensional stability, making the tape very convenient to use.

BASIC USES

- The tapes are recommended to be used for side & end overlaps of HDPE membrane to achieve excellent bonding and sealing of the overlap joints.

FEATURES AND BENEFITS

- Excellent Mechanical Strength and Dimensional Stability.

AVAILABILITY

- Contact your Local Tremco Sales Representative.

PACKAGING

- TREMproof® 3700 HD Seal Tape
Length: 20 M, Width: 80 mm and 100 mm,
Thickness: 0.6mm

APPLICATION TECHNIQUE

- For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion result

STORAGE

Store tapes in dry & clean conditions and in their original, closed wrapping away from sources of chemical contamination, damage, ignition sources and open flame.

SHELF LIFE

1 year when stored in accordance with storage instructions.



TECHNICAL DATA (TYPICAL VALUES at 25°C)

| PROPERTY | VALUE |
|--|-------------------------|
| Nominal Thickness ; ASTM D3652 | 600 ± 10% µm |
| Carrier material & Colour | Polyester – Transparent |
| Adhesion to Steel grams/inch; MD/TD; ASTM D 3330 | 2000 Min |
| Adhesion to PE grams/inch; MD/TD; ASTM D 3330 | 2000 Min |
| Rolling Ball Tack cm; ASTM D 3121 | 1-2 |
| Operating Temperatures °C; | 40 - 50 |
| Linear Dimensional Change %; 6hrs @ 70°C;ASTM D 1204 | < 1% |

- Please contact us at info@stoncor-me.com to confirm the most up-to-date Product Data Sheets.
- NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification & Labelling of Chemicals (GHS) requirements.