



# SOLARGARD 6083

## DEVELOPED TO RESTORE LOW SLOPE AND METAL ROOFS

**Solargard 6083** is a premium water-based, acrylic elastomeric roof coating that is durable and flexible even in low temperatures. It offers excellent resistance to weathering and dirt pick-up across a variety of roofing substrates, including metal, weathered single-ply, modified bitumen, polyurethane foam, and smooth built-up roofs. Not only does Solargard 6083 offer waterproofing benefits, but its high solar reflective index provides a optimum cool roof effect.

### FEATURES / BENEFITS

- Significantly lower overall cost
- Increased service life
- Less work, smaller crews, lower labour costs
- Quick and easy application
- Cold-application = safer, more productive workers
- No tear off; no disposal
- Cost effective over second roofing layer
- Restoration can usually be repeated
- Can help dramatically lower energy use





## LIMITATIONS

Not recommended for use over the following:

- **Roof Decks:** Direct applications to cementitious wood fibre, metal, poured-in-place gypsum, structural lightweight or lightweight insulating concrete, and wood decks (includes plywood, tongue-and-groove, etc.).
- **Products / Systems:** Asphalt-based or coal tar gravel surfaced BUR systems, clay tile, expanded or extruded polystyrene insulation, fluoropolymer finished metal, shingles, silicone-based products, and tar-based products.
- Not for use under continuous immersion or prolonged (longer than 48 hours) ponding water.
- Not recommended for areas of high pedestrian traffic.
- Consult Tremco Roofing sales representative for trafficable or walkway solutions.

## PACKAGING

18.9 litre

## STORAGE

- 12 Months shelf life in unopened containers, when properly stored. **DO NOT FREEZE!**
- Recommended storage is indoors in a ventilated, dry area removed from heat, open flame, ignition sources and direct sunlight. Storage temperatures should range from 15°C to 21°C and must not drop below 0°C or exceed 43°C.
- On the jobsite, materials should remain on the pallet until use and be stored in a shaded, ventilated area. Materials should be covered with a light-coloured, reflective tarp for protection against the elements. Allow for adequate air flow inside the pallets.
- Shelf life could be affected if the product is not stored properly.

## TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyse conditions and needs to develop recommendations for special applications.